Balanced Asphalt Mixture Design – A Formula for Success






October 18, 2017 Hartford, Connecticut

Shane Buchanan



Discussion Items

- 1. What is Balanced Mix Design (BMD)?
- 2. Why the need for BMD?
- 3. What are the most common performance tests (rutting and cracking) for BMD?
- 4. What is the current national state of practice for BMD?
- 5. How does a BMD compare with a volumetric mix design?
- 6. What about acceptance testing with a BMD approach?
- 7. What is the future of BMD?





What is Balanced Mix Design (BMD)?



Balanced Mix Design Definition

 "Asphalt mix design using performance tests on appropriately conditioned specimens that address multiple modes of distress taking into consideration mix aging, traffic, climate and location within the pavement structure."



Use the right mix for the job!



1890

- Barber Asphalt Paving Company
- •Asphalt cement 12 to 15% / Sand 70 to 83% / Pulverized carbonite of lime 5 to 15%

_ |•:

- ·Clifford Richardson, New York Testing Company
- •Surface sand mix: 100% passing No. 10, 15% passing No. 200, 9 to 14% asphalt
- •Asphaltic concrete for lower layers, VMA terminology used, 2.2% more VMA than current day mixes or ~0.9% higher binder content

1920s

- · Hubbard Field Method (Charles Hubbard and Frederick Field)
- ·Sand asphalt design
- •30 blow, 6" diameter with compression test (performance) asphaltic concrete design (Modified HF Method)

Stability

1927

- •Francis Hveem (Caltrans)
- ·Surface area factors used to determine binder content; Hveem stabilometer and cohesionmeter used
- ·Air voids not used initially, mixes generally drier relative to others, fatigue cracking an issue

Stability + Durability

1943

1993

- •Bruce Marshall, Mississippi Highway Department
- •Refined Hubbard Field method, standard compaction energy with drop hammer
- Initially, only used air voids and VFA, VMA added in 1962; stability and flow utilized

Stability + Durability

Superpave

- Level 1 (volumetric)
- Level 2 and 3 (performance based, but never implemented)

Why the need for BMD?



Why the Need for a New Mix Design Approach?

• Problems:

- Dry mixes exist in some areas.
- Volumetrics alone can not adequately evaluate mix variables, such as recycle, warm-mix additives, polymers, rejuvenators, and fibers.

Solutions:

- Recognize performance issues related to dry mixes in some areas.
 (Note: Many performance issues are caused by factors outside the mix design.)
- 2. Increase understanding of the factors which drive mix performance
- 3. **Design for performance** and not just to "the spec".
- Start thinking outside of long held "rules and constraints"
- 5. Innovate!









Pavement Performance General Overview

 Achieving Balanced Mixture Performance is Key to a Long Lasting Pavement















What Type Distress Is Occurring?





Agencies Are Searching for Solutions: Spec Changes


- Superpave system is becoming unrecognizable with specifications changing rapidly as agencies search for ways to improve durability
- Specifications have become convoluted and confounded
- Existing specified items compete against each other
- New requirements get added and nothing gets removed
- Establishing true "cause and effect" is impossible






What is the Main Key to Enhancing the Durability of Asphalt Mixtures?


- "Volume of Effective Binder (Vbe) is the primary mixture design factor affecting both durability and fatigue cracking resistance."
 - Vbe = VMA Air Voids








What are the most common performance tests (rutting and cracking) for BMD?





Test Mixtures in the Lab to Help Ensure Field Performance

• Mixtures need to be evaluated in the lab during design to help ensure the required field performance can be achieved.





Main Pavement Distresses Observed in the Field

- Rutting
 - Rutting in asphalt mixture(s) layers (focus of rutting performance testing)



- Fatigue cracking
 - Bottom-up cracking
 - Top-down cracking



- Reflection Cracking
 - Cracking from underlying cracks/joints



- Shrinkage of mixture due to low temperatures
- Moisture Damage (Stripping)









Stability Testing (Rutting)







Rutting Tests

 Rutting can be evaluated with several available tests based on the user preference.



Hamburg Wheel Test (HWT)



Asphalt Pavement Analyzer (APA)



AMPT Flow Number



Durability Testing (Cracking)










First Question for Durability Testing: What is the Anticipated Mode of Distress for Testing?

- Many test are available with each targeting a specific specimen response (i.e., field distress)
- Typical distress modes
 - Fatigue cracking (top down/bottom up)
 - Low temperature (thermal) cracking
 - Reflection (reflective) cracking
- Various empirical and mechanistic tests are available for use.
- Match apples to apples, not apples to oranges!







GOALS

- 1. MATCH THE TEST TO THE DISTRESS
- 2. SET APPROPRIATE FAILURE THRESHOLDS



Fatigue (Bottom Up or Top Down) Related **Cracking Tests**





Bottom Up

Bending Beam Fatigue

Bottom Up



Texas Overlay Test

Bottom Up / Top Down



SCB

- LTRC Jc
- IFIT

Bottom Up



Direct Tension Cyclic Fatigue, S-VECD



Thermal Cracking Tests



IDT Creep Compliance



TSRST



SCB at Low Temp



Disk Shaped Compact Tension (DCT)



Reflection (Reflective) Cracking Tests



Disk Shaped Compact Tension (DCT)



Texas Overlay Test




SCB (IFIT)



Performance Tests

- **Empirical** tests will tend to have monotonic loading + high strains and can be conducted in a shorter time period.
- Mechanistic tests will tend to have cyclic loading + low strains and will require a longer test time.
- Each test is developed to evaluate a certain mixture response.
- Use caution when trying to relate one test to another (e.g., IFIT vs DCT).



Key Test Considerations


- 1. Strong relationship to performance
- 2. Practical: cost, time, complexity
- 3. Repeatable, reproducible



What is the current national state of practice for BMD?




Agency Practices For Balanced Mix Design





BMD Approaches


- Three general mix design approaches.
- Volumetric Design w/ Performance Verification
- Performance Modified Volumetric Design
- 3. Performance Design






Graphic Developed by Kevin Hall (FHWA BMD Task Force), 2016


Volumetric Design w/ Performance Verification



Performance Modified Volumetric Design



Performance Design



What Typically Drives a State Agency Practice?

- SHAs are selecting different performance tests.
- Variance is driven by 1) different pavement distress considerations (e.g., thermal cracking in Minnesota versus top-down cracking in Florida) and 2) intended mix application or mix component of interest (e.g., specialty mixes or high recycle mixes).
- BMD approaches vary, and will likely continue to vary, in the future.
 - Not unexpected...
 - How many states currently use AASHTO M323 without any modification? Not many!
















BMD Basic Example – Volumetric Design w/ Performance Verification

Texas DOT

- Volumetric design conducted
- Hamburg Wheel Tracking Test (HWTT) AASHTO T 324
- Overlay Tester (OT) Tex-248-F
- Three asphalt binder contents are used: optimum, optimum +0.5%, and optimum -0.5%.
- The HWTT specimens are shortterm conditioned.
- The OT specimens are long-term conditioned.





Within this acceptable range (5.3 to 5.8 percent), the mixture at the selected asphalt content must meet the Superpave volumetric criteria.

Ongoing National Research: NCHRP Project 20-07/Task 406

- Development of a Framework for Balanced Asphalt Mixture Design
 - 1 yr. / 100k Project, Started May 2017
- The objective of this research is to develop a framework that addresses alternate approaches to devise and implement balanced mix design procedures incorporating performance testing and criteria.
- The framework shall be presented in the format of an AASHTO recommended practice and shall encompass a wide variety of testing procedures and criteria.

Framework for Balanced Mix Design NCHRP 20-07/Task 406





Ongoing State DOT Research

- BMD is a very "hot" topic nationally!
- Various State DOTs have current research activities focused on BMD related activities

State DOT	Research Title			
California	Simplified Performance Based Specifications for Long Life AC Pavements			
Idaho	Development and Evaluation of Performance Measures to Augment Asphalt Mix Design in Idaho			
Indiana	Performance Balanced Mix Designs for Indiana's Asphalt Pavements			
Minnesota	Balanced Design of Asphalt Mixtures			
Texas	Develop Guidelines and Design Program for Hot-Mix Asphalts Containing RAP, RAS, and Other Additives through a Balanced Mix Design Process			
Wisconsin	 Analysis and Feasibility of Asphalt Pavement Performance-Based Testing Specifications Regressing Air Voids for Balanced HMA Mix Design 			















How does a BMD compare with a volumetric mix design?




Balanced Mix Design is Really Nothing Totally New!


• Many similarities with older design approaches.

Step	Marshall	Hveem ▼	Balanced Mix Design
Select Asphalt Binder	YES	YES* (CKE for %)	YES
Select Virgin Aggregate	YES	YES	YES
Select Recycle Content	YES	YES	YES
Compact Specimens at a Range of Binder Contents	YES	YES	YES
Calculate Volumetric Properties	YES	YES	YES
Conduct Stability Performance Testing	YES (Marshall Stability)	YES (Hveem Stabilometer)	YES (User Preference)
Conduct "Durability" Performance Testing	YES (Marshall Flow)	YES (Hveem Cohesiometer)	YES (User Preference for Target Distress)
Evaluation Performance Tests Against Developed Mix Specific Criteria	YES	YES	YES
Select Optimum Binder Content	YES	YES	YES
Determine Volumetric Properties at Optimum Binder Content	YES	YES	YES
Evaluate Moisture Susceptibility at Optimum Binder Content	YES	YES	YES
Control Mixture During Production	YES (Volumetrics)	YES (Volumetrics)	YES (Volumetrics and/or Performance Tests)



Volumetric Mix Design vs Balanced Mix Design (Example)





Note: Example for Illustration Purposes.




Source: NCAT Balanced Mix Design Training Course What about acceptance testing with a BMD approach?



BMD Field Acceptance - Approaches

- Any designed mixture must be produced and controlled to help ensure acceptable field performance.
- Three general field acceptance approaches.
- 1. Volumetric
- 2. Volumetrics + Performance
- 3. Performance








What's the future of BMD?



The Path Forward for Balanced Mix Design

- Long term effort with ups/downs, but we must start now.
- Recognize the need and move incrementally in the appropriate direction to limit risk of mix performance issues.
- Utilize available, proven approaches to find effective, implementable solutions.
- Completion of 20-07 Task 406 and the developed AASHTO recommended practice will aid use / implementation.





Thank You / Questions

Shane Buchanan Asphalt Performance Manager, Oldcastle Materials 205-873-3316

sbuchanan@oldcastlematerials.com



